



Technical Data - CarboQC At-line

Standard methods
ASBC Beer-13D: Dissolved Carbon Dioxide Volume Expansion Method, EBC Chapter 9.28.5, Mebak Chapter 2.26.1.5

Technical Specifications	
Measuring range	
CO₂	0 g/L to 12 g/L (0 vol. to 6 vol.) at 30 °C 0g/L to 20 g/L (0 vol. to 10 vol.) < 15 °C
Temperature	- 3 °C to +40 °C (27 °F to 104 °F), Accuracy: ± 0.2 °C
Pressure	0 bar to 10 bar absolute (0 psi to 145 psi)
Repeatability s.d:	
CO₂	0.04 g/L (0.02 vol.)
Reproducibility s.d:	
CO₂	0.1 g/L (0.05 vol.)
Digital Resolution:	
CO₂	0.01 g/L
Additional information:	
Sample volume	approx. 150 mL
Measuring time per sample	approx. 55 seconds
Internal storage	500 measured results
Interfaces	1 x RS-232 for PC and printer 1 x USB for PC 1 x RFID, 1 x Bluetooth (optional)
Protection class	IP67
Power supply	AC 100 - 240 V, 50/60 Hz, 1.5 A DC 12 V, 3.0 A
Rechargeable battery type	Li-Ion 11.1 V, 2.25 Ah (optional: Li-Ion 11.25 V, 2.6 Ah)
Maximum at-line operation	10 hours